## DETAILED ESTIMATE FOR THE CONSTRUCTION OF 200 CFT CAPACITY SEPTIC TANK AT.......IN THE DISTRICT OF ------- UNDER ------ DIVISION VIDE DRAWING NO.- 181 SL NO. 303 DATED 25-04-79

DE DRAWING NO.- 181 SL NO. 303 DATED 25-04-VIDE S/R OF B.C.D.BIHAR, w.e.f. 15-09-2014

	•	VIDE 3/K OF B.C.D.BITAN, W.E.I. 13-03-2014	
SI.no.	SR.Item No.	Items of work	Total Quantity
1	2	3	4
1	2.8.1.	Earthwork in excavation in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m: All kinds of soil  Tank- 1x16'-0" x 7'-6"x 7'-0" = 840 Cft.  Chamber- 2x(3'-4"x 5'-2"x2'-9") = 95 Cft.  Masonry Pillar- 1x 2'-1"x2'-1"x0'-6" = 2 Cft 937 Cft Or 26.54 M³	26.54 M <sup>3</sup>
2	11.72	Providing designation 100A one brick flat soling joints filled with local sand including cost of watering, taxes, royalty all complete as per building specification and direction of E/I.  Tank- 1x16'-0"x 7'-6" = 120 Sft.  Chamber- 2x 3'-10"x 5' -2" = 40 Sft.  160 Sft. Or 14.87 M <sup>2</sup>	14.87 M <sup>2</sup>
3	4.1.3	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering all work up to plinth level: 1:2:4 (1 Cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size)  Tank- 1x 16'-0" x 7'-6"x 0'-9" = 90 Cft.  Chamber- 2x3'- 10"x 5'-2"x 0'-6" = 20 Cft.  Masonry Pillar- 1x 2'-1"x2'-1"x 0'-6" = 2 Cft  112 Cft Or 3.17 M <sup>3</sup>	3.17 M <sup>3</sup>
4	6.1.12/A	Brick work with bricks of class designation 100A in foundation and plinth in : Cement mortar 1:4(1 cement : 4 coarse sand) $ \frac{15" \text{ Thick wall}}{\text{Tank - }} 2 \times 15' - 0" = 30' - 0" \\ 2 \times 4' - 0" = \frac{8' - 0"}{38' - 0"} \\ 38' - 0" \times 1' - 3" \times 5' - 0" = 237 \text{ Cft.} $ $ \frac{10" \text{ Thick wall}}{2x + 14' - 7"} = 29' - 2" \\ 2x + 14' - 7" = 29' - 2" \\ 2x + 14' - 5" = \frac{8' - 10"}{38' - 0"} \\ 38' - 0" \times 0' - 10" \times 2' - 3" = 71 \text{ Cft.} $ $ \frac{\text{Chamber-}}{2x + 2x + 2} 2x + 2' - 6" = \frac{5' - 0"}{19' - 2"} \\ 2x + 12' - 6" = \frac{5' - 0"}{19' - 2"} $ Quantity- $19' - 2" \times 0' - 10" \times 3' - 3" = 52 \text{ Cft.}$ Masonry Pillar- $1 \times 1' - 8" \times 1' - 8" \times 3' - 0" = \frac{8 \text{ Cft.}}{368 \text{ Cft. Or. } 10.42 \text{ M}^3} $	10.42 M <sup>3</sup>
5	5.1.3	Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centering, shuttering, finishing and reinforcement-All work up to plinth level: 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size) Septic Tank Cover  In Baffle wall (3" thick:-)  2x4'-10"x4'-0"x 0'-3" = 10 Cft.  1x4'- 10"x3'-3"x 0'-3" = 4 Cft.  Slab Cover (3" thick)  Tank- 1x13'-9"x 5'-3"x 0'-3" = 18 Cft.  In Chambers 2 Nos  2x3'-6½" x 3'-4 "x 0'-3" = 6 Cft.  38 Cft.  Or 1.08 M³	1.08 M <sup>3</sup>

6	5.22.7A	Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete: Thermo-Mechanically Treated bars(TMTC-500) 8mm dia  Qty- 38 Cft @ 2.00 kg per Cft. Including weight of lifting rings needed.  Qty. = 38x 2.00 = 76 kg	76 kg
7	19.15.1	Providing M.S. foot rests including fixing in manholes with 20x20x10 cm cement concrete blocks 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) as per standard design : With 20x20 mm square bar In Septic tank- 6 Nos.	6 Nos.
8	12.78.1	Providing and fixing on wall face unplasticised-PVC (working pressure 4 kg per sq cm) pipes conforming to IS: 4985 including jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansion: 75mm diameter PVC pipe- 14'-0" = 14 Rft. Or 4.27 Mt	4.27 Mtr.
9	12.79.5.1	Providing and fixing on wall face unplasticised- PVC moulded fittings /accessories for unplasticised-PVC rain water pipes conforming to IS: 4985 including jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansion: 75 mm bend	1 No.
10	N.S.I.	Providing and fixing on wall face unplasticised- PVC moulded fittings /accessories for unplasticised-PVC rain water pipes conforming to IS: 4985 including jointing with seal ring conforming to IS: 5382 leaving 10 mm gap for thermal expansion: 75mm dia PVC Cowel.	1 No.
11	12.79.4.2	Providing & fixing on wall face unplastisised P.V.C. pipe (working pressure 4 Kg/Sq.cm) confirming to IS-4985 for sewerage including jointing with seal ring confirming to IS:5382 leaving 10mm gap for thermal expansion:110 x 110 x 110mm dia Single Jn Tee without door	1 No.
12	PH Code 7205 Analysed	Providing & fixing on wall face unplastisised P.V.C. pipe (working pressure 4 Kg/Sq.cm) confirming to IS-4985 for sewerage including jointing with seal ring confirming to IS:5382 leaving 10mm gap for thermal expansion:  110 x 110 x110mm single equal Y without door	1 No.
13	13.17.1	12mm cement plaster of mix:  1:3 (1 cement : 3 coarse sand) : Neat Cement Punning  Tank- Bottom - 1 x 12'- 6" x 4'-0" = 50 Sft.  In side 2 x (12'-6"+4'-0")x5'-0" = 165 Sft.  2x(12'-11"+ 4'-5")x2'-2½" = 77 Sft.  Chamber- Bottom - 2 x 2'- 6"x2'-6" = 13 Sft.  In side - 2x2 x 2' - 8½"x 3' - 0" = 33 Sft  In side - 2 x2x 2' - 6" x 3' - 0" = 368 Sft  Or. 34.20 M²	34.20M <sup>2</sup>
14.	13.11.4	12mm cement plaster of mix: 1:6 (1 Cement : 6 coarse sand)  Tank Out side - 2 x 14'-7" = 29'- 2"  Side Projections- 2x2x0'-11½" = 3'-10"  33'-0"x 2'-3" = 74 Sft.  Top of Tank - 2x14' -7" = 29'-2"  29'-2" x 0'-5" = 12 Sft  Chamber Out sides -  (2x2x3'- 6½"+2x4'-2")x1'-9" = 39 Sft Top of  Chamber (2x2x3'-6½"+2x1x3'-4")x0'- 5"= 09sft.  Massonary Pillar - 4 x 1' - 8" x 3' - 0" = 20 Sft.  1x 1' - 8" x 1' - 8" = 03 Sft.  157 Sft.  Or 14.59 M²	14.59 M <sup>2</sup>

15	13.24.2	6mm cement plaster to ceilling of Mix :  1:4 (1 cement : 4 coarse sand)  R.C.C.Cover of tank- 1x12' -11"x 4' -5" = 57 Sft.  R.C.C.Cover of  Chamber - 2 x 2'- 6" x 2'- 8½" = 14 Sft.  71 Sft. Or 6.60 M²	6.60 M <sup>2</sup>
16	19.9.1.1	Providing and fixing in position pre-cast R.C.C. manhole cover and frame of required shape and approved quality:LD 2.5:Rectangular shape 600x450 mm internal dimensions	1 Nos.
17		Extra cost :- (a) Bricks - 5630 Nos. (b) Cement - 48 Bags.	- 5630 Nos 48 Bags.
18		Carriage of materials :-         (a) Bricks -       5630 Nos.         (b) Sand -       4.79 M³         (C) Stone Chips -       3.78 M³	5630 Nos 4.79 M <sup>3</sup> 3.78M <sup>3</sup>

### CONSUMPTION STATEMENT OF MATERIALS FOR 200 C.F.T. SEPTIC TANK.

SI No.	Item of work	Qty.	Cement in M <sup>3</sup>	Coarse Sand in M <sup>3</sup>	Stone Chips in 3	Bricks in Nos.	Steel in Kg.
1	Brick flat soling.	14.87 M <sup>2</sup>	-	0.227	-	480	- -
2	P.C.C. (1:2:4)	3.17 M <sup>3</sup>	0.705	1.411	2.821	-	-
3	Brick work (1:4)	10.42 M <sup>3</sup>	0.521	2.084	-	5147	-
4	R.C.C.(1:2:4)	1.08 M <sup>3</sup>	0.240	0.481	0.961	-	76.00
5	½" C.P. (1:3) with punning	34.20 M <sup>2</sup>	0.130	0.369	-	-	-
6	½" C.P. (1:6)	14.59 M <sup>2</sup>	0.030	0.180	-	-	-
7	1/4" C.P. (1:4) in ceiling	6.60 M <sup>3</sup>	0.009	0.038	-	-	-
Total -			1.635 M <sup>3</sup> = 48 bags	4.79 M <sup>3</sup>	3.782 M <sup>3</sup> Say 3.78 M <sup>3</sup>	5627 Nos Say 5630 Nos.	76 Kg.

(S.N. Verma) Assistant Tech. Secy.

# DETAILED ESTIMATE FOR CONSTRUCTION OF 4'-0" DIA & 10'-0" DEEP SEPTIC TANK IN-------P..S. IN THE DISTRICT OF ------ DIVISION

### VIDE S/R OF B.C.D.BIHAR, w.e.f. 15-09-2014 (TO BE TAKEN 2 NOS FOR 200 CFT.CAPACITY TANK)

Clro	Class CD liams literas of world					
Sl.no.	SR.Item No.	Items of work	Total Quantity			
1	2	3	4			
1	2.8.1.	Earthwork in excavation in foundation trenches or drains (not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift up to 1.5 m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m: All kinds of soil (A) $\frac{22}{7x4}$ x $(5'-8")^2$ X $3'-0" = 75.51$ Cft. $\frac{22}{7x4}$ x $(4'-0")^2$ X $2'-0" = \frac{25.14}{100.65}$ Cft. Or $2.85$ M <sup>3</sup> (B) DoDo- below 5' - 0" upto 8' - 0" depth. $\frac{22}{7x4}$ x $(4'-0")^2$ X $3'-0" = 37.71$ Cft. Or $1.068$ M <sup>3</sup>	4.63 M <sup>3</sup>			
		(C) ) DoDo- below 8' - 0" upto 10' - 0" depth.	,			
2	5.1.3	Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centering, shuttering, finishing and reinforcement-All work up to plinth level: 1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size)  In Baffle wall (2" thick:-)  22 x (5'-8")² X 0'-3" = 6.29 Cft.  7x4 Or 0.178 M³	0.178 M <sup>3</sup>			
3	5.29.7A	Reinforcement for R.C.C. work including straightening, cutting, bending, placing in position and binding all complete: Thermo-Mechanically Treated bars(TMTC-415) 8mm dia. R.C.C. same as item 5.1.3 Qty- 6.29 Cft 2.00 kg per Cft. Including from lifting rings needed.  Qty. = 12.58 kg say 13 kg	13 kg			
.4	13.11.4	12mm cement plaster of mix: 1:6 (1 Cement : 6 coarse sand) Ground Floor -  22 x 5 '- 8" X 1'-0" = 17.80 Sft.  7  Or 1.654 M <sup>2</sup>	1.654 M <sup>2</sup>			

5	13.24.2	6mm cement plaster to ceiling of Mix : 1:4 (1 cement : 4 coarse sand)  22 x (5 '- 8") <sup>2</sup> = 25.17 Sft.  7x4	2.753 M <sup>2</sup>
		$\frac{22}{7 \times 5' - 8" \times 0' - 3"} = \frac{4.45 \text{ Sft}}{29.62 \text{ Sft.}}$ Or 2.753 M <sup>2</sup>	
6		Extra cost :- (a) Bricks - 663 Nos. (b) Cement - 3 Bags.	- 663 Nos 3 Bags.
7		Carriage of materials :-  (a) Bricks - 1573 Nos.  (b) Sand - 0.40 M³  (C) Stone Chips - 0.16 M³.	1573Nos 0.40 M <sup>3</sup> 0.16 M <sup>3</sup>
8	Br.	Providing brick bats and filling the same in soak pit as per specification and direction of engineer in charge.  22 x (4'-0") <sup>2</sup> X 8'-6" = 106.85 Cft.  7x4 Say 107 Cft.  Or 3.03 M <sup>3</sup>	3.03 M <sup>3</sup>
9	6.1.14A	Brick work with bricks of class designation 100A in foundation and plinth in : Cement mortar 1:6(1 cement : 6 coarse sand)	1.343 M <sup>3</sup>

### ONSUMPTION STATEMENT OF MATERIALS FOR 4'-0" DIA SOAK PIT.

SI	Item of work	Qty.	Cement	Coarse Sand	Stone Chips	Bricks in	Steel in
No.			in M <sup>3</sup>	in M <sup>3</sup>	in <sup>3</sup>	Nos.	Kg.
1	Brick work in c.m. (1:6)	1.343 M <sup>2</sup>	0.048-	0.288	-	663	-
2	R.C.C. (1:2:4)	0.178 M <sup>3</sup>	0.040	0.079	0.158	-	-
3	Reinforcement	0.013 M./T.	-	-	-	-	13
4	Brick bats	3.03 M <sup>3</sup>	-	-	-	910	-
5	½" C.P. (1:6)	1.654M <sup>2</sup>	0.003	0.020	-	-	-
6	1/4" C.P. (1:4)	2.753 M <sup>2</sup>	0.004	0.016	-	-	-
Total -			0.095 M <sup>3</sup>	0.403 M <sup>3</sup>	0.158 M <sup>3</sup>	1573 Nos.	13 Kg.
			= 3 bags	Say 0.40 M <sup>3</sup>	Say 0.16 M <sup>3</sup>		

Assistant Tech. Secy.